
Tapping and ProStopp™ DS



Equipment Needed to Plug a 6-inch Gas Main to 275 psi CE Compliant and Compatible for Thin Wall Applications


Technical Datasheet - EH Date: July 2023





6-inch Gas Main to 300 psi






Note: Consult your TDW representative for additional fitting options.



Tapping and ProStopp™ DS


Equipment Needed to Plug a 8-inch Gas Main to 275 psi CE Compliant and Compatible for Thin Wall Applications





8-inch Gas Main to 300 psi





Note: Consult your TDW representative for additional fitting options.


TDW

Tapping and ProStopp™ DS

Equipment Needed to Plug a 10-inch Gas Main to 275psi

*10-inch applications use 12-inch equipment


CE Compliant and Compatible for Thin Wall Applications





10-inch Gas Main to 300 psi






Note: Consult your TDW representative for additional fitting options.






Equipment Needed to Plug a 12-inch Gas Main to 275 psi CE Compliant and Compatible for Thin Wall Applications





12-inch Gas Main to 300 psi





Note 1: Consult your TDW representative for additional fitting options.

Note 2: *The 07-1586-0000 Completion Machine with 48" travel is required to set 12" SHORTPLUG™ with Guide Bars in SHORTSTOPP Type II 3-Way™ Tee fittings using the 06-1546-0000 Adapter.