
# **Tapping and ProStopp®DS**




### **Equipment Needed to Plug a 4" Gas Main to 300 psi**





#### 4" Gas Main to 300 psi






Note: Consult your TDW representative for additional fitting options.

# **Tapping and ProStopp®DS**





# **Equipment Needed to Plug a 6" Gas Main to 300 psi**





#### 6" Gas Main to 300 psi






Note: Consult your TDW representative for additional fitting options.

# **Tapping and ProStopp® DS**

# TDW


### **Equipment Needed to Plug an 8" Gas Main to 300 psi**





#### 8" Gas Main to 300 psi





Note 1:\* 8-inch Spool Adapter required to set 8-inch SHORTPLUG™ with Guide Bars in SHORTSTOPP Type II 3-Way™ Tee fittings using the 06-1544-0000 Adapter.


Note 2: Consult your TDW representative for additional fitting options.

# **Tapping and ProStopp® DS**

### **Equipment Needed to Plug a 10" Gas Main to 300 psi**

\*10" applications use 12" equipment








#### 10" Gas Main to 300 psi



See Bulletin 2110.001




Note 1: \*12-inch Spool Adapter required to set 10-inch SHORTPLUG™ with Guide Bars in SHORTSTOPP Type II 3-Way™ Tee fittings using the 06-1546-0000 Adapter and 07-1586-0000 Completion Machine

Note 2: Consult your TDW representative for additional fitting options.

# **Tapping and ProStopp® DS**

# TDW


# **Equipment Needed to Plug a 12" Gas Main to 300 psi**





#### 12" Gas Main to 300 psi





Note 1: Consult your TDW representative for additional fitting options.

Note 2: \*The 07-1586-0000 Completion Machine with 48" travel is required to set 12" SHORTPLUG™ with Guide Bars in SHORTSTOPP Type II 3-Way™ Tee fittings using the 06-1546-0000 Adapter.